



The Real Quality Of Lubricant

BACCHUS EP **Extreme Pressure Grease NLGI-2**

KETERANGAN PRODUK

Bacchus EP-2 merupakan gemuk serba guna yang diformulasikan dengan base lithium sehingga menghasilkan gemuk pelumas yang memiliki kemampuan menahan panas, water proof, friction proof, dapat juga digunakan dalam waktu yang lama dan tetap stabil pada suhu tinggi.

Bacchus EP-2 bisa juga digunakan untuk menggantikan Calcium Grease, Natrium Grease, Alumunium Grease dan lain-lain.

KEISTIMEWAAN

- ✓ Memiliki daya tahan yang kuat terhadap air, tahan oksidasi.
- ✓ Mencegah karat dan korosi.
- ✓ Sangat cocok digunakan pada temperature tinggi.

APLIKASI

- ✓ Dapat digunakan untuk rantai roda pada mesin yang berat. Seperti perlengkapan mobil, motor electric small or medium genset, pompa air, blower dan bisa juga digunakan untuk mengontrol density/thickness.
- ✓ Untuk berbagai peralatan pertambangan dan industri lainnya yang bekerja pada temperature yang rendah maupun tinggi serta lingkungan berat.

KARAKTERISTIK

CHARACTERISTIC	METHODE	UNIT	EP 2
colour			Brown
Texture			Smooth
Soap Type			Lithium
Dropping Point	ASTMD 566	°C	204
Consistency	N.L.G.I		2
Worked Penetration 60 Strokes 100 Strokes	ASTMD 217	Mm/10 25°C	280 7%
Four Ball Weld Load	ASTMD 2596	Kg	260
Timken test Ok Load	ASTMD 2509	Lbs	40
Base Oil Viscosity 40°C 100°C	ASTMD 445	Mm ² /s (cst)	220 17,5
Operating Temperatur			-25 s/d 110

KEMASAN

Pail isi 16 kg dan Drum isi 180 kg

**PRODUCT
DATA
SHEET**